



ARDEX AF 148

All Purpose Flooring Adhesive

Dispersion based

Low odour and very low emissions

Extra-long open time

Suitable for installation of vinyl sheets, vinyl tiles, LVT and carpet tiles

Semi-wet and pressure-sensitive properties

Green Label certified



ARDEX-QUICSEAL SINGAPORE PTE. LTD.

26 Tuas Ave 4 Singapore 639376

Telephone: +65 6861 7700

Fax: +65 6741 4666

Email: sales@ardex-quickseal.com

Website: www.ardex-quickseal.com

ARDEX AF 148

All Purpose Flooring Adhesive

DESCRIPTION

ARDEX AF 148 is a single component, dispersion-based adhesive for laying LVT, PVC and VCT floorings in sheets, tiles, planks and carpet tiles on internal levelled subfloors.

FEATURES & BENEFITS

- Fast: very fast drying time
- Efficient: extremely fast installation of large areas
- Clean: no risk of soiled floor covering
- Versatile application: useable for trowel and roller application
- Can be used as semi-wet and pressure sensitive
- Ease of application with extra-long open time
- Universal: extra-long tack for carpet tile installation up to 24 hours

SURFACE PREPARATION

Subfloors must be level, permanently dry, solid and free from cracks, dirt and adhesion-inhibiting substances.

Apply corresponding ARDEX levelling compounds to achieve a levelled floor.

APPLICATION

Stir ARDEX AF 148 well before using.

Apply evenly on the subfloor with a suitable trowel or roller, work from out of the container and avoid adhesive pools.

Fit flooring after corresponding airing time of ARDEX AF 148 and press down firmly.

After fitting, roll the complete area again with the roller.

NOTE: The specified processing and drying times refer to +20°C and 50% RH. Differing room climate conditions lead to different times.

Do not use ARDEX AF 148 in areas subject to increased moisture, such as entrance areas and wet cells.

COVERAGE

Depending on the surface structure and absorbability of the subfloor. Approximately 190 - 220g/m² with using A1 trowel, on a flat smooth surface. Approximately 80 - 120g/m² with using velour roller on a flat smooth surface. Coverage

may vary if different trowel size is used.

TECHNICAL DATA

Raw material base:	Dispersion-based
Airing time:	<ul style="list-style-type: none">• approx. 30mins on absorbent subfloor• approx. 60mins on non-absorbent subfloor
Working time:	approx. 180 mins
Coverage A1 trowel: Velour Roller:	<ul style="list-style-type: none">• approx. 190 -220 g/m²• approx. 80 -120 g/m²
Cleaning agent:	Water, before the adhesive starts to dry
Storage time:	12 months at room temperature

PACKAGING

ARDEX AF 148 is packed in a 15L plastic pail.

STORAGE AND SHELF LIFE

Stored in the original sealed container, in a dry, cool place, the shelf life of ARDEX AF 148 is 12 months.

SAFETY PRECAUTIONS

Product contains isothiazolones. May produce an allergic reaction. Keep out of reach of children
Irritant: Avoid eye and skin contact. Use only in well ventilated areas. Keep container tightly closed. In case of contact with eyes and skin, rinse with plenty of water. In event of irritation, seek for medical advice according to Safety Datasheet for further information (available upon request and online at www.ardex-quickseal.com)

DISCLAIMER

The technical datasheets are based on the latest information and given in good faith and represent the best of our knowledge and experience at the time of printing. They are primarily offered for user's consideration and evaluation. It is the responsibility of the user to conduct their own tests to validate the suitability of the products. It is also the responsibility of the user to ensure that the products are used and handled correctly and in accordance with any applicable standards, the

ARDEX AF 148

All Purpose Flooring Adhesive

product instructions and recommendations and only for the uses they are intended. As we have no control over site conditions and the execution of the work, we accept no liability for any loss or damage which may rise as a result thereof. We also reserve the right to update the information at any time without prior notice to you to reflect our ongoing research and development.

Offices:

Malaysia:

ARDEX QUICSEAL MALAYSIA SDN. BHD.
No. 35-1, Jalan Puteri 2/3, Bandar Puteri,
47100, Puchong, Selangor Darul Ehsan
Telephone: +603 8069 1139
Telefax: +603 8052 3223
Email: sales@ardex-quicseal.com

Thailand:

ARDEX (THAILAND) CO., LTD
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road
Bangkaew, Bangplee, Samutprakarn 10540 Thailand
Telephone: +66 2316 3069 Fax:+66 2316 3075
Email: sales@ardex.co.th
Website: www.ardex.co.th

Vietnam:

Mobile: +84 901 351 308
Email: sales@ardex-quicseal.com

DEC 2022