



## Safety Data Sheet

according to Regulation (EU) 2015/830

Issue date: 8/22/2016

Revision date: 6/22/2021

Supersedes version of:  
8/22/2016

Version: 2.0

www.ardex.de

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
 Product name : ARDEX P 82 Component A  
 Product code : 59210; 59200

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category : Professional use  
 Industrial/Professional use spec : Construction materials  
 Use of the substance/mixture : Substrate Preparation  
 Function or use category : Construction materials

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

ARDEX GmbH  
 Friedrich-Ebert-Strasse 45  
 D-58453 Witten-Annen - Germany  
 T 0049 (0)2302/664-0 - F 0049 (0)2302/664-355  
[sicherheitsdatenblatt@ardex.de](mailto:sicherheitsdatenblatt@ardex.de) - [www.ardex.de](http://www.ardex.de)

**1.4. Emergency telephone number**

Country	Organisation/Company	Address	Emergency number	Comment
Germany	Vergiftungs-Informations-Zentrale	Breisacher Strasse 86b 79110 Freiburg	+49 (0) 761 19240	For medical information in German and English language

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Skin corrosion/irritation, Category 2 H315  
 Serious eye damage/eye irritation, Category 2 H319  
 Skin sensitisation, Category 1 H317  
 Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

**Adverse physicochemical, human health and environmental effects**

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

: Warning

Hazardous ingredients :

: 2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane, oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Hazard statements (CLP) :

: H315 - Causes skin irritation.  
 H317 - May cause an allergic skin reaction.  
 H319 - Causes serious eye irritation.  
 H412 - Harmful to aquatic life with long lasting effects.

# ARDEX P 82 Component A

## Safety Data Sheet

according to Regulation (EU) 2015/830

Precautionary statements (CLP)	: P102 - Keep out of reach of children. P280 - Wear eye protection, protective gloves. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
EUH-statements	: EUH205 - Contains epoxy constituents. May produce an allergic reaction. EUH208 Contains mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)(55965-84-9), 1,2-benzisothiazol-3(2H)-one(2634-33-5), 2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane(1675-54-3), oxirane, mono[(C12-14-alkyloxy)methyl] derivs.(68609-97-2). May produce an allergic reaction
Extra phrases	: Dispose of contents/container in accordance with regional/national/international/local regulations.

### Labelling according to Directive 67/548/EEC or 1999/45/EC

#### 2.3. Other hazards

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (EC Index-No.) 603-073-00-2 (REACH-no) 01-2119456619-26	> 7,5 - < 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(CAS-No.) 68609-97-2 (EC-No.) 271-846-8 (EC Index-No.) 603-103-00-4 (REACH-no) 01-2119485289-22	< 2,5	Skin Irrit. 2, H315 Skin Sens. 1, H317
formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	(CAS-No.) 9003-36-5 (EC-No.) 500-006-8 (REACH-no) 01-2119454392-40	> 1 - < 3,5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9 (EC Index-No.) 613-088-00-6	> 0,005	Skin Sens. 1, H317 Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Irrit. 2, H315 Aquatic Acute 1, H400
mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	(CAS-No.) 55965-84-9 (EC Index-No.) 613-167-00-5	> 0,00015	Acute Tox. 2 (Inhalation), H330 Acute Tox. 2 (Dermal), H310 Acute Tox. 3 (Oral), H301 Skin Sens. 1A, H317 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (EC Index-No.) 603-073-00-2 (REACH-no) 01-2119456619-26	( 5 ≤C ≤ 100) Eye Irrit. 2, H319 ( 5 ≤C ≤ 100) Skin Irrit. 2, H315
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9 (EC Index-No.) 613-088-00-6	( 0.05 ≤C < 100) Skin Sens. 1, H317
mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	(CAS-No.) 55965-84-9 (EC Index-No.) 613-167-00-5	( 0.0015 ≤C ≤ 100) Skin Sens. 1A, H317 ( 0.06 ≤C < 0.6) Skin Irrit. 2, H315 ( 0.06 ≤C < 0.6) Eye Irrit. 2, H319 ( 0.6 ≤C ≤ 100) Eye Dam. 1, H318 ( 0.6 ≤C ≤ 100) Skin Corr. 1C, H314

Full text of H- and EUH-statements: see section 16

# ARDEX P 82 Component A

## Safety Data Sheet

according to Regulation (EU) 2015/830

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Remove dirty clothes.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do not give an unconscious person anything to drink. If you feel unwell, seek medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: If symptoms persist call a doctor.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause severe irritation.
Symptoms/effects after ingestion	: Irritating to the respiratory system and mucous membranes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Not dangerous.
Explosion hazard	: None.
Reactivity in case of fire	: Product is not explosive.
Hazardous decomposition products in case of fire	: None.

#### 5.3. Advice for firefighters

Precautionary measures fire	: Evacuate area.
Firefighting instructions	: Contain the extinguishing fluids by bunding. Do not allow run-off from fire-fighting to enter drains or water courses.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Absorb spillage to prevent material damage.
------------------	---

##### 6.1.1. For non-emergency personnel

Protective equipment	: Concerning personal protective equipment to use, see section 8.
Emergency procedures	: Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, vapours, spray.

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Do not allow to enter drains or water courses.

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

#### 6.4. Reference to other sections

For further information refer to section 13. See Section 8.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: See Section 8. When mixing the components: Please note the safety data sheet for the second component.
-----------------------------------	--

# ARDEX P 82 Component A

## Safety Data Sheet

according to Regulation (EU) 2015/830

Precautions for safe handling	: Wear personal protective equipment. Avoid contact with skin and eyes. Use only in well ventilated areas.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Store in a well-ventilated place. Keep cool.
Storage conditions	: Store in original container. Protect from sunlight.
Incompatible products	: Oxidizing agent. Strong bases. Strong acids.
Storage area	: Keep out of frost.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)</b>	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	0.04 mg/m <sup>3</sup>
Long-term - local effects, inhalation	0.02 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Acute - local effects, inhalation	0.04 mg/m <sup>3</sup>
Long-term - local effects, inhalation	0.02 mg/m <sup>3</sup>
PNEC (Water)	
PNEC aqua (freshwater)	3.39 µg/l
PNEC aqua (marine water)	3.39 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.027 mg/kg dwt
PNEC sediment (marine water)	0.027 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.01 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	0.23 mg/l
<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0.966 mg/kg bw/day
Long-term - systemic effects, inhalation	6.81 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	1.2 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0.345 mg/kg bw/day
PNEC (Water)	
PNEC aqua (freshwater)	4.03 µg/l
PNEC aqua (marine water)	0.403 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	49.9 µg/kg dw
PNEC sediment (marine water)	4.99 µg/kg dw
PNEC (Soil)	
PNEC soil	3 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	1.03 mg/l

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Personal protective equipment:

Liquid splashes may occur.

#### Hand protection:

Protective gloves

# ARDEX P 82 Component A

## Safety Data Sheet

according to Regulation (EU) 2015/830

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Natural rubber, Latex, Butyl rubber, Nitrile rubber (NBR)	2 (> 30 minutes)	0,1		
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	1		EN ISO 374

### Eye protection:

Safety glasses

Type	Field of application	Characteristics	Standard
Safety goggles	Safety goggles recommended during refilling, Wear security glasses which protect from splashes	Plastic, With side shields	

### Skin and body protection:

Wear suitable protective clothing

Type	Standard
Skin protection appropriate to the conditions of use should be provided, Long sleeved protective clothing	

### Respiratory protection:

No specific measures are necessary. In case of inadequate ventilation wear respiratory protection.



### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Various colours.
Odour	: No data available
Odour threshold	: No data available
pH	: 5 – 8.5
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 100 °C
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 2.3 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1 – 1.1 g/cm <sup>3</sup>
Solubility	: Forms emulsion in presence of water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 100 – 3000 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content	: < 3 % VOC - Swiss ordinance
-------------	-------------------------------

# ARDEX P 82 Component A

## Safety Data Sheet

according to Regulation (EU) 2015/830

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

None.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

None.

#### 10.6. Hazardous decomposition products

No hazardous decomposition products known.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)</b>	
LD50 oral rat	66 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Calculated by reference to active substance, Oral, 14 day(s))
LD50 dermal rat	> 141 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	0.17 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Calculated by reference to active substance, Inhalation (aerosol), 14 day(s))
<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
LD50 oral rat	490 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
<b>oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)</b>	
LD50 oral rat	26800 mg/kg bodyweight (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 4000 mg/kg
<b>formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg

Skin corrosion/irritation : Causes skin irritation.  
pH: 5 – 8.5

Serious eye damage/irritation : Causes serious eye irritation.  
pH: 5 – 8.5

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : May cause irritation to skin.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects.

<b>mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)</b>	
EC50 - Crustacea [1]	0.007 mg/l (48 h, Acartia tonsa, Salt water, Experimental value, GLP)

# ARDEX P 82 Component A

## Safety Data Sheet

according to Regulation (EU) 2015/830

<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
LC50 - Fish [1]	2.18 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	2.94 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Experimental value, Lethal)
ErC50 algae	150 µg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Experimental value, GLP)

<b>formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)</b>	
LC50 - Fish [1]	0.55 mg/l
EC50 - Crustacea [1]	1.6 mg/l
ErC50 algae	1.8 mg/l
NOEC chronic crustacea	0.3 mg/l

### 12.2. Persistence and degradability

<b>ARDEX P 82 Component A</b>	
Persistence and degradability	Not applicable.
<b>mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane (1675-54-3)</b>	
Persistence and degradability	Biodegradability in water: no data available.
<b>oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)</b>	
Persistence and degradability	Readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>ARDEX P 82 Component A</b>	
Bioaccumulative potential	No bioaccumulation.
<b>mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)</b>	
BCF - Fish [1]	41 – 54 (OECD 305: Bioconcentration: Flow-Through Fish Test, 28 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	0.75 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 24 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
BCF - Fish [1]	6.62 (Equivalent or similar to OECD 305, 56 day(s), Lepomis macrochirus, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	-0.9 – 0.99 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane (1675-54-3)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)</b>	
BCF - Fish [1]	160 – 263 (BCFWIN, Estimated value)
Partition coefficient n-octanol/water (Log Pow)	3.77 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.7 – 3.6

### 12.4. Mobility in soil

<b>ARDEX P 82 Component A</b>	
Ecology - soil	No information available.
<b>mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)</b>	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.81 – 1 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.
<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
Surface tension	72.6 mN/m (20 °C, 0.1 %, EU Method A.5: Surface tension)

# ARDEX P 82 Component A

## Safety Data Sheet

according to Regulation (EU) 2015/830

<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.97 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.

<b>oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)</b>	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	> 5.63 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Adsorbs into the soil.

### 12.5. Results of PBT and vPvB assessment

<b>ARDEX P 82 Component A</b>	
PBT: not relevant – no registration required	
vPvB: not relevant – no registration required	

Component	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

Additional information : Do not discharge into drains or the environment. The local official regulations for wastewater treatment must be observed

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Do not put down the drain. Must undergo physico-chemical treatment prior to disposal.  
Product/Packaging disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW) code : 08 04 10 - waste adhesives and sealants other than those mentioned in 08 04 09

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

### 14.6. Special precautions for user

#### - Overland transport

Not regulated

#### - Transport by sea

Not regulated

#### - Air transport

Not regulated

# ARDEX P 82 Component A

## Safety Data Sheet

according to Regulation (EU) 2015/830

### - Inland waterway transport

Not regulated

### - Rail transport

Not regulated

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : < 3 % VOC - Swiss ordinance

#### 15.1.2. National regulations

##### Germany

Regulatory reference : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:

	EUH208
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
EUH205	Contains epoxy constituents. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A

# ARDEX P 82 Component A

## Safety Data Sheet

according to Regulation (EU) 2015/830

---

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

# ARDEX P 82 Component

## B



### Safety Data Sheet

according to Regulation (EU) 2015/830

Issue date: 8/22/2016

Revision date: 6/22/2021

Supersedes version of:  
8/22/2016

Version: 2.0

www.ardex.de

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Product name : ARDEX P 82 Component B  
Product code : 59210; 59200

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use  
Industrial/Professional use spec : Construction materials  
Use of the substance/mixture : Substrate Preparation  
Function or use category : Construction materials

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

ARDEX GmbH  
Friedrich-Ebert-Strasse 45  
D-58453 Witten-Annen - Germany  
T 0049 (0)2302/664-0 - F 0049 (0)2302/664-355  
[sicherheitsdatenblatt@ardex.de](mailto:sicherheitsdatenblatt@ardex.de) - [www.ardex.de](http://www.ardex.de)

### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Germany	Vergiftungs-Informations-Zentrale	Breisacher Strasse 86b 79110 Freiburg	+49 (0) 761 19240	For medical information in German and English language

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 2 H319  
Skin sensitisation, Category 1 H317

Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) : Warning  
Hazardous ingredients : benzyl alcohol, Isophorondiamine, benzyldimethylamine  
Hazard statements (CLP) : H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
Precautionary statements (CLP) : P102 - Keep out of reach of children.  
P280 - Wear eye protection, protective gloves.  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

# ARDEX P 82 Component B

## Safety Data Sheet

according to Regulation (EU) 2015/830

	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
EUH-statements	: EUH205 - Contains epoxy constituents. May produce an allergic reaction.
Extra phrases	: Dispose of contents/container in accordance with regional/national/international/local regulations.

### Labelling according to Directive 67/548/EEC or 1999/45/EC

#### 2.3. Other hazards

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl alcohol	(CAS-No.) 100-51-6 (EC-No.) 202-859-9 (EC Index-No.) 603-057-00-5	< 2,5	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Oral), H302
Isophorondiamine	(CAS-No.) 2855-13-2 (EC-No.) 220-666-8 (EC Index-No.) 612-067-00-9 (REACH-no) 01-2119514687-32	< 2,5	Skin Sens. 1, H317 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
benzyl dimethylamine	(CAS-No.) 103-83-3 (EC-No.) 203-149-1 (EC Index-No.) 612-074-00-7	< 0,2	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 3 (Inhalation:vapour), H331 Skin Corr. 1B, H314 Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Remove dirty clothes.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do not give an unconscious person anything to drink. If you feel unwell, seek medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: If symptoms persist call a doctor.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause severe irritation.
Symptoms/effects after ingestion	: Irritating to the respiratory system and mucous membranes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

# ARDEX P 82 Component B

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Not dangerous.  
Explosion hazard : None.  
Reactivity in case of fire : Product is not explosive.  
Hazardous decomposition products in case of fire : None.

### 5.3. Advice for firefighters

Precautionary measures fire : Evacuate area.  
Firefighting instructions : Contain the extinguishing fluids by bunding. Do not allow run-off from fire-fighting to enter drains or water courses.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spillage to prevent material damage.

#### 6.1.1. For non-emergency personnel

Protective equipment : Concerning personal protective equipment to use, see section 8.  
Emergency procedures : Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, vapours, spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Do not allow to enter drains or water courses.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

### 6.4. Reference to other sections

For further information refer to section 13. See Heading 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : See Heading 8. When mixing the components: Please note the safety data sheet for the second component.  
Precautions for safe handling : Wear personal protective equipment. Avoid contact with skin and eyes. Use only in well ventilated areas.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in a well-ventilated place. Keep cool.  
Storage conditions : Store in original container. Protect from sunlight.  
Incompatible products : Oxidizing agent. Strong bases. Strong acids.  
Storage area : Keep out of frost.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

benzyl alcohol (100-51-6)		
Germany	AGW (OEL TWA) [1]	22 mg/m <sup>3</sup>
Germany	AGW (OEL TWA) [2]	5 ppm

# ARDEX P 82 Component B

## Safety Data Sheet

according to Regulation (EU) 2015/830

benzyl alcohol (100-51-6)		
Germany	Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; 11 - Summe aus Dampf und Aerosolen

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

No specific measures are necessary. In case of inadequate ventilation wear respiratory protection.



#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: milky.
Odour	: No data available
Odour threshold	: No data available
pH	: 5 – 8.5
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 23 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1 – 1.1 g/cm <sup>3</sup>
Solubility	: Forms emulsion in presence of water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 100 – 3000 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

# ARDEX P 82 Component B

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 9.2. Other information

VOC content : < 3 % VOC - Swiss ordinance

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

None.

### 10.6. Hazardous decomposition products

No hazardous decomposition products known.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

benzyl alcohol (100-51-6)	
LD50 oral rat	1620 mg/kg bw/day (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg (EPA OTS 798.1100, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 4.18 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, (maximum achievable concentration), Inhalation (aerosol), 14 day(s))

Isophorondiamine (2855-13-2)	
LD50 oral rat	1030 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 5.01 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

benzyl dimethylamine (103-83-3)	
LD50 oral rat	579 mg/kg bodyweight (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	1477 mg/kg (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	2.05 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

Skin corrosion/irritation : Causes skin irritation.  
pH: 5 – 8.5

Serious eye damage/irritation : Causes serious eye irritation.  
pH: 5 – 8.5

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : No data available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

# ARDEX P 82 Component B

## Safety Data Sheet

according to Regulation (EU) 2015/830

<b>benzyl alcohol (100-51-6)</b>	
LC50 - Fish [1]	460 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	230 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	770 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
<b>Isophorondiamine (2855-13-2)</b>	
LC50 - Fish [1]	110 mg/l (EU Method C.1, 96 h, Leuciscus idus, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	23 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h - Algae [1]	37 mg/l (EU Method C.3, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Cell numbers)
<b>benzyl dimethylamine (103-83-3)</b>	
LC50 - Fish [1]	37.8 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	> 100 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	1.34 mg/l (EU Method C.3, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

### 12.2. Persistence and degradability

<b>ARDEX P 82 Component B</b>	
Persistence and degradability	Not applicable.
<b>benzyl alcohol (100-51-6)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
<b>Isophorondiamine (2855-13-2)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>benzyl dimethylamine (103-83-3)</b>	
Persistence and degradability	Not readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>ARDEX P 82 Component B</b>	
Bioaccumulative potential	No bioaccumulation.
<b>benzyl alcohol (100-51-6)</b>	
BCF - Fish [1]	1.37 l/kg (BCFBAF v3.01, Estimated value)
Partition coefficient n-octanol/water (Log Pow)	1 – 1.1 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Isophorondiamine (2855-13-2)</b>	
BCF - Fish [1]	1.827 – 3.16 (BCFBAF v3.01, Pisces, Estimated value)
Partition coefficient n-octanol/water (Log Pow)	0.99 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>benzyl dimethylamine (103-83-3)</b>	
BCF - Fish [1]	2.1 – 22 (OECD 305: Bioconcentration: Flow-Through Fish Test, 6 week(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	1.98 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

<b>ARDEX P 82 Component B</b>	
Ecology - soil	No information available.
<b>benzyl alcohol (100-51-6)</b>	
Surface tension	39 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.122 – 1.332 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Highly mobile in soil.
<b>Isophorondiamine (2855-13-2)</b>	
Surface tension	3470 mN/m (23 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.97 (log Koc, QSAR)
Ecology - soil	Low potential for adsorption in soil.

# ARDEX P 82 Component B

## Safety Data Sheet

according to Regulation (EU) 2015/830

<b>benzylidimethylamine (103-83-3)</b>	
Surface tension	61.47 mN/m (EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.955 – 2.457 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

### 12.5. Results of PBT and vPvB assessment

Component	
benzyl alcohol (100-51-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Isophorondiamine (2855-13-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
benzylidimethylamine (103-83-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

Additional information : Do not discharge into drains or the environment. The local official regulations for wastewater treatment must be observed

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Do not put down the drain. Must undergo physico-chemical treatment prior to disposal.  
Product/Packaging disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW) code : 08 04 10 - waste adhesives and sealants other than those mentioned in 08 04 09

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

### 14.6. Special precautions for user

#### - Overland transport

Not applicable

#### - Transport by sea

Not applicable

#### - Air transport

Not applicable

#### - Inland waterway transport

Not applicable

#### - Rail transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

# ARDEX P 82 Component B

## Safety Data Sheet

according to Regulation (EU) 2015/830

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances

VOC content : < 3 % VOC - Swiss ordinance

### 15.1.2. National regulations

#### Germany

Regulatory reference : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)  
Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids  
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
EUH205	Contains epoxy constituents. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*