



---

# ARDEX AF 365

## Timber Adhesive For Teakwood Floor

---

Ready to use

Excellent initial wet tack and grab

Good bond strength

Gap filling function for sub-floor installations



**ARDEX-QUICSEAL SINGAPORE PTE. LTD.**

26 Tuas Ave 4 Singapore 639376

Telephone: +65 6861 7700

Fax: +65 6741 4666

Email: [sales@ardex-quickseal.com](mailto:sales@ardex-quickseal.com)

Website: [www.ardex-quickseal.com](http://www.ardex-quickseal.com)

# ARDEX AF 365

## Timber Adhesive for Teakwood Floor

### DESCRIPTION

ARDEX AF 365 is a single-component, PVA polymer based emulsion adhesive for bonding plywood sub-floor, teakwood strip. It adheres to most types of wood, parquet and sheet timber flooring systems to concrete, timber or over existing floor.

### SPECIAL PROPERTIES

- Ready to use
- Excellent initial wet tack and grab
- Good bond strength
- Gap filling function for sub-floor installations

### APPLICATION

- Bonding plywood sub-floor onto concrete and cement screed
- Teakwood and parquet bonding
- As an universal wood adhesive, to bond most porous materials together

### SURFACE PREPARATION

All substrates must be level, smooth, permanently dry, structurally sound, firm, load-bearing, free from curing compounds, cracks and also free of excess moisture/alkali and all substances (oil, wax, grease, paint, oil based sealers and etc). Concrete surfaces should be removed by scabbling or grit blasting to produce a sound surface.

### DIRECTION FOR USE

#### Mixing

Adhesive can be used neat or with little of water dilution, approx. 3% by weight.

#### Application

ARDEX AF 365 should be applied evenly to the suitably prepared substrate using a notch trowel. Place wood strips, planks or plywood directly into the wet adhesive firmly, interlocking with tongue or groove of the next strip or plank. Anchor down with concrete nails to hold the wood strips down whilst the adhesive sets.

### DRYING TIME

Allow the finished assembly to dry, cure and harden fully at least 7 - 10 days before sanding and application of lacquer.

### TECHNICAL DATA

Product Identity	
Form:	Milk white liquid
Solid content (by weight):	> 48.5
Viscosity:	25 - 35 x 10 <sup>4</sup> cps
pH:	4 - 6

### COVERAGE

Depending on the texture and absorbency of the floor, the coverage will be approx. 25 - 30m<sup>2</sup> per 20kg.

### PACKAGING

ARDEX AF 365 is packed in 20kg carton.

### STORAGE AND SHELF LIFE

Stored in cool, dry shaded warehouse, away from rain and sunlight. When stored under the correct conditions, ARDEX AF 365 will have a shelf life of 12 months.

### SAFETY PRECAUTIONS

Avoid contact with skin and eyes; in case of contact with the eyes, rinse immediately with plenty of water and seek medical advice; wear suitable gloves and keep the product out of the reach of children. Consult the relevant Safety Datasheet for further information and available upon request and online at [www.ardex-quickseal.com](http://www.ardex-quickseal.com).

### DISCLAIMER

The technical datasheets are based on the latest information and given in good faith and represent the best of our knowledge and experience at the time of printing. They are primarily offered for user's consideration and evaluation. It is the responsibility of the user to conduct their own tests to validate the suitability of the products. It is also the responsibility of the user to ensure that the products are used and handled correctly and in accordance with any applicable standards, the product instructions and recommendations and only for the uses they are intended. As we have no control over site conditions and the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. We also reserve the right to update the information at any time without prior notice to you to reflect our ongoing research and development program.

# ARDEX AF 365

## Timber Adhesive for Teakwood Floor

---

### Offices:

#### Malaysia:

ARDEX QUICSEAL MALAYSIA SDN. BHD.  
72-2, Jalan Puteri 2/2 Bandar Puteri 47100,  
Puchong, Selangor Darul Ehsan  
Malaysia  
Phone: +603 8051 0311  
Email: sales.malaysia@ardex-quicseal.com

#### Thailand:

ARDEX (THAILAND) CO., LTD  
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road  
Bangkaew, Bangplee, Samutprakarn 10540 Thailand  
Telephone: +66 2316 3069 Fax:+66 2316 3075  
Email: sales@ardex.co.th  
Website: www.ardex.co.th

#### Vietnam:

Mobile: +84 901 351 308  
Email: sales@ardex-quicseal.com

DEC 2022 R1 T