



---

# ARDEX E 26

## Admixture for Self-Smoothing Compound

---

Ready for use

Improves tensile strength for high-traffic application

Improves surface hardness and walkability

Solvent-free

Green Label certified



**ARDEX-QUICSEAL SINGAPORE PTE. LTD.**

26 Tuas Ave 4 Singapore 639376

Telephone: +65 6861 7700

Fax: +65 6741 4666

Email: [sales@ardex-quickseal.com](mailto:sales@ardex-quickseal.com)

Website: [www.ardex-quickseal.com](http://www.ardex-quickseal.com)

# ARDEX E 26

## Admixture for Self-Smoothing Compound

### DESCRIPTION

ARDEX E 26 is a single component milky white synthetic resin dispersion, when mixed with ARDEX Floor Levelling Products improves tensile strength for high traffic applications.

### AS A MORTAR ADMIX

ARDEX E 26 is recommended to mix with ARDEX Floor Smoothing levelling compound.

It will provide higher tensile strength, greater elasticity and improve the walkability and surface hardness as a result of additional synthetic binding.

### MIXING

The mixing ratio for ARDEX E 26 is based on the highest water dosage recommendation in respective Floor Smoothing Levelling Compound product data sheet. May increase 2% - 3% more of total mixing dosage to achieve better flow and consistency.

Example:

A 25 kg of ARDEX CL 5 bag should be mixed with a maximum of 6 kg of ARDEX E 26.

\*Do not add water to ARDEX E 26.

### PACKAGING

ARDEX E 26 is supplied in 18kg jerry can and 150kg drum.

### STORAGE AND SHELF LIFE

ARDEX E 26 has a shelf life of 12 months when stored in the original unopened packaging and away from direct sunlight.

### SAFETY PRECAUTIONS

Avoid contact with skin and eyes; in case of contact with the eyes, rinse immediately with plenty of water and seek medical advice; wear suitable gloves and keep the product out of the reach of children. Avoid generation of airborne dust during mixing. Additional information is in the material Safety Data Sheet (SDS) available upon request and online at [www.ardex-quickseal.com](http://www.ardex-quickseal.com)

### DISCLAIMER

The technical datasheets are based on the latest information and given in good faith and represent the best of our knowledge and experience at the time of printing. They are primarily offered for user's consideration and evaluation. It is the responsibility of the user to conduct their own tests to validate the suitability of the products. It is also the responsibility of the user to ensure that the products are used and handled correctly and in accordance with any applicable standards, the product instructions and recommendations and only for the uses they are intended.

We also reserve the right to update the information at any time without prior notice to you to reflect our ongoing research and development program.

#### OFFICES:

Malaysia:

ARDEX QUICSEAL MALAYSIA SDN. BHD.  
72-2, Jalan Puteri 2/2 Bandar Puteri 47100,  
Puchong, Selangor Darul Ehsan  
Malaysia  
Phone: +603 8051 0311  
Email: [sales.malaysia@ardex-quickseal.com](mailto:sales.malaysia@ardex-quickseal.com)

Thailand:

ARDEX (THAILAND) CO., LTD  
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road  
Bangkaew, Bangplee, Samutprakarn 10540 Thailand  
Telephone: +66 2316 3069 Fax: +66 2316 3075  
Email: [sales@ardex.co.th](mailto:sales@ardex.co.th)  
Website: [www.ardex.co.th](http://www.ardex.co.th)

Vietnam:

Mobile: +84 901 351 308  
Email: [sales@ardex-quickseal.com](mailto:sales@ardex-quickseal.com)

Feb 2025 T