



---

# ARDEX P 51 RFU

## Water-based Primer

---

Ready for use primer

Bonding agent



**ARDEX-QUICSEAL SINGAPORE PTE. LTD.**

26 Tuas Ave 4 Singapore 639376

Telephone: +65 6861 7700

Fax: +65 6741 4666

Email: [sales@ardex-quickseal.com](mailto:sales@ardex-quickseal.com)

[www.ardex-quickseal.com](http://www.ardex-quickseal.com)

# ARDEX P 51 RFU

## Water-based Primer

### DESCRIPTION

Water-based primer. Aqueous synthetic polymer based dispersion.

### SUBFLOOR PREPARATION

Substrates must be dry, protected by a functioning DPM, firm and free from dust, water soluble materials, excess adhesive residues and other barriers to adhesion.

Surface contamination such as residues of polish, wax, grease, etc. should be removed using ARDEX DGR degreaser prior to suitable mechanised preparation. ARDEX P 51 RFU is not recommended for use on metal and mastic asphalt, excess adhesive residues, ARDEX DPM, polyurethane and epoxy coatings.

### APPLICATION

Ensure that the ambient temperature and the temperature of the surface being primed are above 5°C. If ARDEX P 51 RFU is used where moisture sensitive materials are to be subsequently applied, the substrate must be dry, i.e. with flooring materials the screed should have a RH reading not greater than 75% and, where direct to ground, protected by an effective damp-proof membrane. Apply the priming coat evenly with a soft broom or brush, over the sound, clean and dust-free surface and leave to dry thoroughly to a clear, thin film before beginning any subsequent work.

### COVERAGE

5 kg of ARDEX P 51 RFU will cover approx. 30m<sup>2</sup>.

### PACKAGING

5 kg, 20 kg and 200 kg

### STORAGE

When stored under the correct conditions and unopened, ARDEX P 51 RFU has a shelf life of 12 months.

### SAFETY PRECAUTIONS

Keep out of reach of children Irritant: Avoid eye and skin contact. In case of contact with eyes and skin, rinse with plenty of water. In event of irritation, seek for medical advice according to the material Safety Data

Sheet which is available upon request and online at [www.ardex-quicseal.com](http://www.ardex-quicseal.com)

### DISCLAIMER

The technical datasheets are based on the latest information and given in good faith and represent the best of our knowledge and experience at the time of printing. They are primarily offered for user's consideration and evaluation. It is the responsibility of the user to conduct their own tests to validate the suitability of the products. It is also the responsibility of the user to ensure that the products are used and handled correctly and in accordance with any applicable standards, the product instructions and recommendations and only for the uses they are intended. As we have no control over site conditions and the execution of the work, we accept no liability for any loss or damage which may rise as a result thereof. We also reserve the right to update the information at any time without prior notice to you to without prior notice to you to reflect our ongoing research and development program.

### OFFICES:

Malaysia:  
ARDEX QUICSEAL MALAYSIA SDN. BHD.  
72-2, Jalan Puteri 2/2 Bandar Puteri 47100,  
Puchong, Selangor Darul Ehsan  
Malaysia  
Phone: +603 8051 0311  
Email: [sales.malaysia@ardex-quicseal.com](mailto:sales.malaysia@ardex-quicseal.com)

Thailand:  
ARDEX (THAILAND) CO., LTD  
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road  
Bangkaew, Bangplee, Samutprakarn 10540 Thailand  
Telephone: +66 2316 3069 Fax: +66 2316 3075  
Email: [sales@ardex.co.th](mailto:sales@ardex.co.th)  
Website: [www.ardex.co.th](http://www.ardex.co.th)

Vietnam:  
Mobile: +84 901 351 308  
Email: [sales@ardex-quicseal.com](mailto:sales@ardex-quicseal.com)

July 2024 T