QUICSEAL 109 PRIMER

Bituminous Primer

Excellent penetration and sealing of porous surfaces

Enhances adhesion of waterproofing membranes

Suitable for various substrates

Easy to apply by brush or spray

Fast drying for quicker installation

Ready to use and provides good coverage

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
26 Tuas Ave 4 Singapore 639376
Telephone: +65 6861 7700
Fax: +65 6741 4666
Email: sales@ardex-quicseal.com
Website: www.ardex-quicseal.com

QUICSEAL 109 PRIMER

Bituminous Primer

DESCRIPTION
QUICSEAL 109 PRIMER is a thin black solvent based bituminous priming solution designed to penetrate and seal porous surfaces to provide and prepare a base for waterproofing protection systems.

USES
Suitable to many substrates including metal, slate, concrete, asbestos cement and lightweight concrete screeds, prior to the application of many bituminous materials including torch-on and self adhesive bituminous membrane.

SURFACE PREPARATION
Surfaces must be dry and clean; free from dust, dirt, grease, moss, lichen or any other foreign matter.

APPLICATION
QUICSEAL 109 PRIMER can be brush applied or spray applied to dry surfaces. Stir emulsion well before use. Ensure that only an even thin coating is applied. Ensure QUICSEAL 109 PRIMER has fully penetrated the substrate. Prime twice if substrate is porous. Allow for the solvent to evaporate before application of other materials.

CLEANING TOOLS
Spillage and tools should be cleaned with Paraffin (Kerosene) or white spirit

TECHNICAL DATA

Flash Point (Abel Closed)	> 23°C
Relative Density @ 15°C	0.90 to 0.95kg / ltr
Drying Time	Approximately 20mins to 2 hrs
Solvent Content (depending on type)	Approximately 50% to 55%

PACKAGING: 20 litre

COVERAGE: Concrete 6.5 - 10m^2/litre

*Actual coverage may vary due to condition of the substrate

HANDLING & STORAGE
Store in a cool, dry area, keep away from sources of ignition and normal precautions against fire must be taken. Store only in original container.

HEALTH & HAZARD
Maintain good standards of personal hygiene. Ensure adequate ventilation during application. Do not eat, drink or smoke whilst using this product, Do not use near sources of ignition. Avoid breathing vapours and skin and eye contact.

IMPORTANT NOTES
The information set forth herein is furnished in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact ARDEX-QUICSEAL

Offices:

Malaysia:
ARDEX QUICSEAL MALAYSIA SDN. BHD.
72-2, Jalan Puteri 2/2 Bandar Puteri 47100,
Puchong, Selangor Darul Ehsan
Malaysia
Phone: +603 8051 0311
Email: sales.malaysia@ardex-quicseal.com

Thailand:
ARDEX (THAILAND) CO., LTD
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road
Bangkaew, Bangplee, Samutprakarn 10540 Thailand
Telephone: +66 2316 3069 Fax:+66 2316 3075
Email: sales@ardex.co.th
Website: www.ardex.co.th

Vietnam:
Mobile: +84 901 351 308
Email: sales@ardex-quicseal.com

Reference No. QS109Primer/220520 T