QUICSEAL 202

Overlapping Super 0311 Tape

Excellent adhesion to multiple substrates

Provides a vapour- and moisture-tight seal

Flexible with ± 20% movement capability

Easy and quick to apply

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
26 Tuas Ave 4 Singapore 639376
Telephone: +65 6861 7700
Fax: +65 6741 4666
Email: sales@ardex-quicseal.com
Website: www.ardex-quicseal.com

QUICSEAL 202

Overlapping Super 0311 Tape

USES

Used as an overlapping tape for QUICSEAL SUPER DPM to ensure a vapour / moisture tight joint.
Application of QUICSEAL SUPER 0311 in relation to QUICSEAL SUPER DPM to ensure a vapour / moisture tight properties.

APPLICATION OF QUICSEAL SUPER 0311 IN RELATION TO QUICSEAL SUPER DPM

QUICSEAL SUPER 0311 is introduced to ensure a complete continuous seal against vapour or moisture migration. Surfaces to be joined must be clean and dry. Adjacent sheets must be overlapped by a minimum of 100mm and joined by QUICSEAL SUPER 0311.

METHOD OF INSTALLATION OF QUICSEAL SUPER DPM

QUICSEAL SUPER DPM is used either between compacted hard-core bed and base concrete or lean concrete to concrete slab. Care should be taken to ensure that the membrane is not stretched / displaced when placing the concrete or screed over the membrane. Sufficient allowance should be made to avoid areas of unsupported membrane during screeding operation.

TYPICAL PROPERTIES OF QUICSEAL 202

Composition	Blend of synthetic rubbers and insert fillers
Colour	White, teak, black, grey
Tolerances	Thickness ±10%. Width up to 15mm ± 1mm. Between 15mm and 25mm ± 1.5mm. Over 25mm ± 2 mm.
Movement	± 20%
Joint Movement	> 400% at 100mm/min
Adhesive	Excellent to polyethylene, aluminium, steel, glass, wood plastics
Dynamic Tensile	1.9 kg/cm² Peel 6 kg per 25mm width
Adhesive Force to	0.7 kg/cm²
Compress by 20%	
Density	1.48 gm/cm² white/1.42gm/cm² black & teak
Service Temperature	-40°C to + 90°C
Durability	20 years plus
Shelf Life	1 year in dry conditions at 20°C
UV Resistance	Very good
Chemical Resistance	Good to dilute acids/alkalis. Poor to organic solvents
Toxicity	No known hazards
Water Absorption	Nil
Moisture Vapour	0.25g/m²
Transmission	
Application	By hand direct from roll, removing paper
Surface Preparation	Contaminant free

PACKAGING

Size:

- 1mm x 12mm x 45m /roll
- 1mm x 25mm x 30m /roll (supplied on request with minimum order quantity)
- 3mm x 30mm x 10m /roll (supplied on request with minimum order quantity)

IMPORTANT NOTES

The information set forth herein is furnished in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact ARDEX-QUICSEAL

QUICSEAL 202
Overlapping Super 0311 Tape

Offices:

Malaysia:
ARDEX QUICSEAL MALAYSIA SDN. BHD.
72-2, Jalan Puteri 2/2 Bandar Puteri 47100,
Puchong, Selangor Darul Ehsan
Malaysia
Phone: +603 8051 0311
Email: sales.malaysia@ardex-quicseal.com

Thailand:
ARDEX (THAILAND) CO., LTD
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road
Bangkaew, Bangplee, Samutprakarn 10540 Thailand
Telephone: +66 2316 3069 Fax:+66 2316 3075
Email: sales@ardex.co.th
Website: www.ardex.co.th

Vietnam:
Mobile: +84 901 351 308
Email: sales@ardex-quicseal.com

Reference No: QS 202/151220 T