QUICSEAL 203

Bitumen Compressible Sealant Strip

Excellent sealing against dust, air, water, and vibration

Flexible and compressible for tight joint filling

Waterproof and weather-resistant

Easy and quick installation

MANAGEMENT SYSTEM CERTIFICATION
DNV
ISO 9001 • ISO 14001

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
26 Tuas Ave 4 Singapore 639376
Telephone: +65 6861 7700
Fax: +65 6741 4666
Email: sales@ardex-quicseal.com
Website: www.ardex-quicseal.com

QUICSEAL 203

Bitumen Compressible Sealant Strip

DESCRIPTION

QUICSEAL 203 is a general-purpose, preformed sealing strip which comprise of flexible bitumen impregnated foam. When compressed, it provides a continuous seal against dust, draughts, dampness and vibration.

USES

QUICSEAL 203 is suitable for sealing gaps or joints in the following applications.

Building Systems

- As a compression seal for Panes, Tilt-Lift, Prefab Sections Precast Panels, CurtainWall Partitions,etc

Roofs

- Lap joints in corrugated roofing.

Air-Conditioning

- Gasket sealing in Refrigeration Ducts, Ventilation Cabinets, Cold Room

Transport

- Compression seal in Motor Vehicles, Caravans, Railcars, etc.

SURFACE PREPARATION & APPLICATION

Brush out and remove all dust and loose particles from all contact surfaces. Sound substrates usually do not require priming. Where necessary, prime porous or uneven substrates with QUICSEAL Bitumen Primer. Place QUICSEAL 203 in position and press firmly into position.

TECHNICAL DATA

Product Type	Flexible bitumen impregnated foam
Service Temperature	Stable within range (-48°C to + 74°C)
Colour	Black
Recovery (Elasticity)	Expands to fill joint narrower than its width when compressed
Water Tightness	No water leakage after 24 hrs at 1m waterhead (under compression)
Fire Resistance	Does not support combustion
Toxicity	Non-toxic in normal use

PACKAGING

QUICSEAL 203 is packed in boxes
Supply dimensions : 25mm x 25mm x 2m (100 mtr per box)

STORAGE

Store in a sheltered, cool, dry place, protected from rain and sunlight and extreme temperatures. QUICSEAL 203 has a shelf life of 12 months when stored as stated in its original packaging.

IMPORTANT NOTES

The information set forth herein is furnished in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact ARDEX-QUICSEAL

Offices:

Malaysia:
ARDEX QUICSEAL MALAYSIA SDN. BHD.
72-2, Jalan Puteri 2/2 Bandar Puteri 47100,
Puchong, Selangor Darul Ehsan
Malaysia
Phone: +603 8051 0311
Email: sales.malaysia@ardex-quicseal.com

Thailand:
ARDEX (THAILAND) CO., LTD
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road
Bangkaew, Bangplee, Samutprakarn 10540 Thailand
Telephone: +66 2316 3069 Fax:+66 2316 3075
Email: sales@ardex.co.th
Website: www.ardex.co.th

QUICSEAL 203

Bitumen Compressible Sealant Strip

Vietnam:
Mobile: +84 901 351 308
Email: sales@ardex-quicseal.com

Reference No.: QS 203/080124 T