QUICSEAL 405

Water Drip Line Former / Crack Inducer Triangle

Crack Inducer & Water Drip Line Former

High Impact UPVC Profile

Effective Concrete Joint Control

Reduces Maintenance Costs

Weather Resistant

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
26 Tuas Ave 4 Singapore 639376
Telephone: +65 6861 7700
Fax: +65 6741 4666
Email: sales@ardex-quicseal.com
Website: www.ardex-quicseal.com

QUICSEAL 405

Water Drip Line Former / Crack Inducer Triangle

USES

- At the base of concrete as transverse control joints and contraction joints
- Forming of water drip-lines or feature groove
- Forming of angled lines or chamfered edges




STANDARDS

QUICSEAL 405 is manufactured from specially developed unplastisized polyvinyl chloride (UPVC) materials which conform to the general requirements of DSTM D-1784-92 with very high impact strength and weather resistant properties.

DESCRIPTION

QUICSEAL 405 is manufactured from specially developed unplastisized polyvinyl chloride triangle piece of 2 metre length designed for inducing crack for effective control of control joints in concrete paved areas. This effective control will reduce maintenance cost. The installation is a simple 'stick them on' application. Simply lay the QUICSEAL 405 and use cement mortar to hold it in position. Proceed to complete the concreting of the paved areas once the holding mortar sets.

PACKING & SECTIONAL DIMENSIONS

Standard Length		Packing Quantity
	3 metre	100 Length/Pack
	2 metre	100 Length/Pack
	2 metre	50 Length/Pack

TECHNICAL INFORMATION OF HIGH IMPACT RIGID PVC

PROPERTY/ TEST METHOD	UNIT	VALUE
Tensile Strength (ASTM D-638)	kg/cm^2	440
Elongation at Break (ASTM D-638)	%	175
Impact Strength (ASTM D-265)	$kg/cm/cm^2$	65
Flexural Strength (ASTM D-790)	kg/cm^2	570
Flexural Modulus (ASTM D-790)	kg/cm^2	235
Stiffness Properties (ASTM D-1525 of Temperature)	°c	71
Vicat Softening Point (ASTM D-1525)	°c	93
Specific Gravity (ASTM D-792)	-	1.38
Accelerated Heat (ASTM D-3045 Ageing 168 hrs @ 70°c after test for Tensile Strength & Elongation)	°c	+7%

IMPORTANT NOTES

The information set forth herein is furnished in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact ARDEX-QUICSEAL

QUICSEAL 405

Water Drip Line Former / Crack Inducer Triangle

Offices:

Malaysia:
ARDEX QUICSEAL MALAYSIA SDN. BHD.
72-2, Jalan Puteri 2/2 Bandar Puteri 47100,
Puchong, Selangor Darul Ehsan
Malaysia
Phone: +603 8051 0311
Email: sales.malaysia@ardex-quicseal.com

Thailand:
ARDEX (THAILAND) CO., LTD
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road
Bangkaew, Bangplee, Samutprakarn 10540 Thailand
Telephone: +66 2316 3069 Fax:+66 2316 3075
Email: sales@ardex.co.th
Website: www.ardex.co.th

Vietnam:
Mobile: +84 901 351 308
Email: sales@ardex-quicseal.com

Reference No.:QS405/260520 T