QUICSEAL 408

uPVC TILE TRIM

Perforated patterns in QUICSEAL Tile Trim sections ensure maximum anchorage under the tile adhesive or cement grout

Good fire (does not support combustion) and impact resistance

Does not support fungal growth

Replace the conventional use of cove tiles that are prone to chipping and staining

Easy to install with no sharp edges

MANAGEMENT SYSTEM CERTIFICATION
DNV
ISO 9001 • ISO 14001

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
26 Tuas Ave 4 Singapore 639376
Telephone: +65 6861 7700
Fax: +65 6741 4666
Email: sales@ardex-quicseal.com
Website: www.ardex-quicseal.com

QUICSEAL 408

uPVC TILE TRIM

DESCRIPTION
QUICSEAL 408 Tile Trim is made from high quality unplasticised polyvinyl chloride (uPVC) materials and offers high impact strength and surface hardness. QUICSEAL 408 is available in a wide range of colours to match popular sanitary fittings and tile colours.


USES
As a stopper / decorative finish at edge of tiles to provide better alignment of tiles.

INSTALLATION INSTRUCTION
1. Select the Tile Trim profile according to requirement.
2. Cut or mitre QUICSEAL 408 to required length with an aid of a cutter or sharp cutter.
3. Install the QUICSEAL 408 Tile Trim and ensure that it is securely embedded into the tile adhesive or cement grout.
4. Align the edge of the tiles with QUICSEAL 408 tile trim and ensure that the gap is constant along the entire length of the trim.
5. After laying the tiles, fill the joint between the tile and QUICSEAL 408 completely with grout.

TECHNICAL DATA

PROPERTY/ TEST METHOD	UNIT	MPE-077
Specific Gravity ASTM D-792	-	1.35 ± 0.05
Vicat Softening Point (1Kgf load) ASTM D-1525	°C	90 ± 5
Thermal Stability B.S. 2782	Mins	30 ± 5

TILE TRIM PROFILE



DIMENSIONS
A: 28 mm B: 9.5 mm

PACKING
Length:
QUICSEAL 408 is available in lengths of 8 ft and 9 ft.
Pack size:
100 lengths per box

IMPORTANT NOTES
The information set forth herein is furnished in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact ARDEX-QUICSEAL

Offices:

Malaysia:
ARDEX QUICSEAL MALAYSIA SDN. BHD.
72-2, Jalan Puteri 2/2 Bandar Puteri 47100,
Puchong, Selangor Darul Ehsan
Malaysia
Phone: +603 8051 0311
Email: sales.malaysia@ardex-quicseal.com

Thailand:
ARDEX (THAILAND) CO., LTD
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road
Bangkaew, Bangplee, Samutprakarn 10540 Thailand
Telephone: +66 2316 3069 Fax:+66 2316 3075
Email: sales@ardex.co.th
Website: www.ardex.co.th

Vietnam:
Mobile: +84 901 351 308
Email: sales@ardex-quicseal.com

Reference No.: QS408/270520 T