QUICSEAL 507

Cure Shield WB

Easy to apply – by spraying, roller or brushing

Improves the quality of the applied concrete or cement-sand substrate Reduction in water loss minimise surface shrinkage and cracking of exposed surfaces

Eliminates the need for damp hessian or polyethylene sheets for curing

Can be applied over with finishes, eg. paint, render, tiled over etc

Supplied ready for immediate use

Green product certified material

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
26 Tuas Ave 4 Singapore 639376
Telephone: +65 6861 7700
Fax: +65 6741 4666
Email: sales@ardex-quicseal.com
Website: www.ardex-quicseal.com

QUICSEAL 507

Cure Shield WB

DESCRIPTION
Cure Shield WB is a specially formulated water-based curing compound for concrete, plasters, repair mortars, floor hardeners, etc.

USES
Cure Shield WB is excellent for use as a moisture-retaining coating to improve the curing of concrete and cement-sand based substrates by reducing water loss.

APPLICATION
Stir contents thoroughly before using. Apply Cure Shield WB evenly by spray, roller or brush at a rate of 5.5 m^2 per litre on newly cast concrete or cement-sand substrates or upon the removal of formwork on vertical surfaces when surface water is no longer present and initial set has commenced.

TECHNICAL DATA

Supply Form	White or blue flowing liquid
Flash Point	Not flammable, water borne
Non-Volatile Content	31 $\pm$ 5%
Density	1.03 $\pm$ 0.03 @ 25°C
Application Temperature	10°C to 60°C
Drying Time	< 1 hour @ 25°C, 65% RH
Water Retention	< 0.55 kg/m^2
Application Rate	5.5 m^2/litre

COVERAGE
Apply Cure Shield WB evenly by spray, roller or brush at a rate of 5.5 m^2 per litre

PACKAGING
Cure Shield WB is supplied in 20 ltr & 210 ltr drums.

STORAGE
12 months in a cool sheltered and ventilated place in the original packaging.

IMPORTANT NOTES
The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact ARDEX-QUICSEAL

Offices:

Malaysia:
ARDEX QUICSEAL MALAYSIA SDN. BHD.
72-2, Jalan Puteri 2/2 Bandar Puteri 47100,
Puchong, Selangor Darul Ehsan
Malaysia
Phone: +603 8051 0311
Email: sales.malaysia@ardex-quicseal.com

Thailand:
ARDEX (THAILAND) CO., LTD
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road
Bangkaew, Bangplee, Samutprakarn 10540 Thailand
Telephone: +66 2316 3069 Fax:+66 2316 3075
Email: sales@ardex.co.th
Website: www.ardex.co.th

Vietnam:
Mobile: +84 901 351 308
Email: sales@ardex-quicseal.com

Reference No. QS 507/300726T