QUICSEAL 646

Hydro-adhesive

Strong bonding performance

Water-based and easy to use

Fast drying (15 – 20 minutes)

Suitable for various substrates

Good coverage and cost-effective

MANAGEMENT SYSTEM CERTIFICATION
DNV
ISO 9001 · ISO 14001

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
26 Tuas Ave 4 Singapore 639376
Telephone: +65 6861 7700
Fax: +65 6741 4666
Email: sales@ardex-quicseal.com
Website: www.ardex-quicseal.com

QUICSEAL 646

Hydro-adhesive

DESCRIPTION
QUICSEAL 646 is a specially formulated water-based adhesive for bonding a wide range of substrates.

USES
- Bonding QUICSEAL 406 Polycel Type K to concrete or masonry substrate.
- Adhering PVC backed carpet tiles, PVC Film, glazed tiles, metal, plastic etc. substrates

SUBSTRATE PREPARATION
The substrates must be clean and sound, free of dust and loose particles. All loose particles, oil, grease, paint, wax or any substance that may inhibit adhesion must be removed.
Apply a thin layer of QUCSEAL 646 evenly by roller or brush. Allow drying for 15 to 20 minutes before pressing applied surfaces together to ensure full contact.

TECHNICAL DATA

Product Type	Liquid
Colour	Milky white
Density of Mix	1.01 g/ml
Viscosity (Rion Viscometer)	17 Poise
Flash Point	Not Applicable

COVERAGE
Approximately 10 - 16m^2 per kg

CLEANING
Rinse hands and tools with abundant amount of water.

PACKAGING
QUICSEAL 646 is supplied in 5, 20 kg pails.

STORAGE
Shelf life of QUICSEAL 646 is 6 months if stored at temperatures between 4°C – 30°C

IMPORTANT NOTES
The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact ARDEX-QUICSEAL

Offices:

Malaysia:
ARDEX QUICSEAL MALAYSIA SDN. BHD.
72-2, Jalan Puteri 2/2 Bandar Puteri 47100,
Puchong, Selangor Darul Ehsan
Malaysia
Phone: +603 8051 0311
Email: sales.malaysia@ardex-quicseal.com

Thailand:
ARDEX (THAILAND) CO., LTD
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road
Bangkaew, Bangplee, Samutprakarn 10540 Thailand
Telephone: +66 2316 3069 Fax:+66 2316 3075
Email: sales@ardex.co.th
Website: www.ardex.co.th

Vietnam:
Mobile: +84 901 351 308
Email: sales@ardex-quicseal.com

Reference No. QS 646/230520 T