QUICSEAL 714

Non Slip Aggregate

Provides a skid resistance and abrasion resistance surface

Moh hardness 9

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
26 Tuas Ave 4 Singapore 639376
Telephone: +65 6861 7700
Fax: +65 6741 4666
Email: sales@ardex-quicseal.com
Website: www.ardex-quicseal.com

QUICSEAL 714

Non Slip Aggregate

DESCRIPTION

QUICSEAL 714 Non Slip Aggregate is a non-ferrous metallic hard-wearing aggregate. It is specially designed to be used in combination with QUICSEAL coatings to provide a non-slip system. QUICSEAL 714 is suitable as an anti-slip material in a wide range of coating systems.

USES

- Floor areas that are frequently or continually wet
- Storage areas
- Shopping centers/motels/schools/theatres/hospitals/sidewalks
- Residential floors
- Areas subjected to severe traffic and wear
- Loading docks
- Industrial floors
- Ramps

SURFACE PREPARATION

Dry Shake (Sprinkle on)

Broadast the QUICSEAL 714 at a coverage of 0.2 - 0.4kg/m^2 onto a freshly applied surface. Leave the applied area to cure for at least 12 hours. Remove the excess aggregates by sweeping and apply a 2nd coat to encapsulate the aggregates and leave it to dry for at least 24 hours before opening to traffic. Coverage will vary depending on desired profile

TECHNICAL DATA

Product Type	Finely divided crystal particles
Colour	White
MOH Hardness	9

PACKAGING

Packing Size : 5kg per bag, 25kg per bag

STORAGE

The shelf life of QUICSEAL 714 is 24 months when stored unopened package in a cool and dry place.

HEALTH & SAFETY

Gloves and goggles should be worn. Any splashes to the skin or eyes should be washed off with clean water. In the event of prolonged irritation, seek medical advice. Areas of use should be well ventilated. Refer to MSDS for further information.

IMPORTANT NOTES

The information set forth herein is furnished in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact ARDEX-QUICSEAL

Offices:

Malaysia:
ARDEX QUICSEAL MALAYSIA SDN. BHD.
72-2, Jalan Puteri 2/2 Bandar Puteri 47100,
Puchong, Selangor Darul Ehsan
Malaysia
Phone: +603 8051 0311
Email: sales.malaysia@ardex-quicseal.com

Thailand:
ARDEX (THAILAND) CO., LTD
969 2nd Floor, Moo 13, Soi 45, Bangna-Trad Road
Bangkaew, Bangplee, Samutprakarn 10540 Thailand
Telephone: +66 2316 3069 Fax:+66 2316 3075
Email: sales@ardex.co.th
Website: www.ardex.co.th

Vietnam:
Mobile: +84 901 351 308
Email: sales@ardex-quicseal.com

Reference No.: QS 714/210520 T